

marantz
PROFESSIONAL

www.marantzpro.com

PHONE: [401] 658.5766

rhox
networking

(61) 3051-5800

<https://loja.rhox.com.br>



Sound Live 8 8-Channel / 2-Bus Tabletop Mixer

Key Features:

- 5 XLR inputs with Marantz Professional microphone preamps
- Dynamic compression (Channels 1-2)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED
- USB audio connectivity with level control
- 100 studio-grade digital effects
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs
- Headphone out with independent level control
- USB jack to power lamps or charge mobile devices

Overview:

The Sound Live 8 is a compact 8-channel/2-bus tabletop mixer that easily handles all the equipment, switching and signal shaping you need to produce first-rate recordings, without the expense, bulk and inconvenience of an overly-complicated studio console.

Among the full roster of professional-caliber features are 5 XLR inputs with ultra-clean sounding Marantz Professional mic pre-amps, Dynamic compression (channels 1 and 2) 60mm faders with mute switch, 100 studio-grade digital effects and a 9-band EQ for main and monitor outputs.

It all adds up to a space-saving desktop mixer with no-compromise audio performance and connection versatility that results in top-quality productions coupled with unsurpassed ease-of-use.

Specifications:

- Mono Input Channels
 - Microphone inputs: Electronically balanced, discrete input configuration
 - Frequency response: 20 Hz to 20 kHz, +0.5 dB
 - THD+N: <0.005% at 0 dBu, 1 kHz
 - Gain range: 0 dB to 45 dB (Mic)
 - SNR: 105 dB
- Line Inputs
 - Electronically balanced
 - Frequency response: 20 Hz to 20 kHz, +0.25 dB
 - THD+N: <0.005% at 0 dBu, 1 kHz
 - Sensitivity range: -15 dBu to 30 dBu
- Impedances
 - Microphone inputs: 51.1 K Ω
 - Channel insert return: 200 K Ω
 - All other inputs: >100 K Ω
 - 2-Track outputs: 10 K Ω
 - All other outputs: 20 K Ω
- Equalization
 - High-shelving: ± 15 dB @ 12 kHz
 - Mid-bell (mono): ± 15 dB @ 2.5 kHz
 - Low-shelving: ± 15 dB @ 80 Hz
 - Main EQ: 9 EQ bands (63 Hz, 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, 16 kHz), ± 15 dB
- DSP
 - A/D & D/A converters: 24-bit
 - DSP Resolution: 24-bit
 - Effects: 10 DSP effects families with 10 variations available per family
 - Presets: 100 total
 - Controls: Rotary encoder preset selector, DSP mute switch, peak LED indicator
- Main Mix
 - Noise (bus noise): -102 dB (ref: +4 dBu, fader 0 dB, channels muted)
 - Noise (bus noise): -91 dB (ref: +4 dBu, fader 0 dB, all input channels assigned and set to "unity" gain)

Sound Live 8

- Phantom Power: Mic Pin2/Pin3 and Pin1 47±2V
- General
 - Mains voltage: USA/Canada: 100–120 VAC ~60 Hz
 - Mains voltage: UK/Australia: 240 VAC ~50 Hz
 - Mains voltage: Europe: 210–240 VAC ~50 Hz
 - Dimensions: 12.0" x 13.6" x 3.1" (305 mm x 346 mm x 80 mm)
 - Weight: 7.7 lbs. (3.5Kg)