



## DN-700R Network SD/USB Audio Recorder

### Key Features:

- Records to SD/SDHC and USB media in MP3 and WAV (up to 24-bit/96kHz)
- Dual Record feature (records to two media options simultaneously for primary and backup recording)
- Relay Record feature (continues recording to backup media when primary media is full)
- File Archiving via FTP (Automatic or Timed) with 24/7 record feature
- Web Remote for setup and control with Password Protection
- Independent switchable XLR Mic/Line inputs with +48V Phantom Power
- Timer recording/playback (30 schedules available)
- IP, RS-232c, GPIO, USB keyboard remote control
- Front panel USB keyboard connection
- NTP supported (Network Time Protocol)
- EDL marking & file edit functions (Move, Copy, Combine and Divide)
- Record monitor (listen the recorded signal while recording)
- Large, bright OLED display
- DMP Mark Editor software included (Windows only)
- Compatible with Denon Professional Product Manager software
- 100-230V switching power supply
- Removable rack kit

### Overview:

Taking its place as Denon Professional's flagship recording product, the DN-700R Network SD/USB Recorder is designed to meet the needs of the most demanding installations, combining high quality audio recording with extensive network capabilities. With a powerful feature set and using the most reliable solid state recording media, the

### Specifications:

- File Format Specifications
  - Compatible media: SD/USB memory/USB HDD
  - Playable formats, file systems: SD, USB: FAT16/FAT32/HFS+
  - Playable WAV Format
    - Extension: WAV, AIFF, AIF
    - Resolution: 16 bit, 24 bit
    - Sampling frequency: 96, 48, 44.1 kHz
  - Playable MP3 Format
    - Extension: MP3
    - Bit rate: 32 – 320 kbps and VBR
    - Sampling frequency: 48, 44.1 kHz
  - Playable AAC Format
    - Extension: M4A
    - Compression method: AAC-LC
    - Bit rate: 64 – 320 kbps and VBR
    - Sampling frequency: 48, 44.1 kHz
- Audio Specifications
  - Number of channels: 2 (stereo), 1 (mono)
  - Audio frequency characteristics: 20 Hz – 20 kHz (+0.5 dB / -1 dB)
  - S/N ratio: More than 89 dB (A-Weighted)
  - Total harmonic distortion: Less than 0.01 %
  - Dynamic range: More than 106 dB (for 24 bit WAV playback)
  - Channel separation: Less than -90 dB
  - Variable pitch width: -16 % – +16 %
  - Variable trim adjustment width: ±2.0 dB
- INPUT - Balanced Analog IN L/R
  - Type: XLR (1:GND, 2:Hot, 3:Cold)
  - Input level: +4 dBu
  - Maximum input level: +24 dBu/+20 dBu/+18 dBu
  - Input impedance: 20 kΩ
- INPUT - Unbalanced Analog IN L/R
  - Type: RCA terminal
  - Input level: -10 dBV
  - Maximum input level: +10 dBV/+6 dBV/4 dBV
  - Input impedance: 10 kΩ
- INPUT - Unbalanced Digital IN
  - Type: RCA terminal
  - Input impedance: 75 Ω

DN-700R allows AV installation professionals to replace traditional recording devices with superior solid state hardware in the widest range of applications.

Housed in a compact 1U rack-mountable chassis, the DN-700R offers recording to both reliable SD card (two slots) and USB storage media. The unit can be configured for 'dual' simultaneous recording to both formats or 'relay/cascade' recording where longer recording times are desirable.

Designed for professional environments, the DN-700R features versatile connectivity including balanced XLR analogue audio and AES/EBU digital I/O, as well as unbalanced analog connections and SPDIF. A remote mic head amp is also available.

For integration into complex installation scenarios, the DN-700R allows network connection via DLNA/UPnP, alongside powerful Web/IP control and direct FTP access. Archiving via network can be performed automatically or at pre-programmed times. Scheduling is also supported, as is NTP (Network Time Protocol).

The DN-700R can be controlled using a variety of remote control interfaces including Parallel GPIO, RS-232c and even a network using its built-in Web Remote. This web-based interface allows a user full control of the DN-700R from setup menus to transport control and hot start playback—even from mobile browsers. This provides complete access to the recorder located in remote areas and when the installation is not always easily accessible.

For direct control, the front panel is designed for ease of use with a bright OLED display and large function buttons offering fast, simple front panel operation. A USB Keyboard input allows file name editing.

The DN-700R also offers programmable timer operation for both recording and playback functions.

Denon Professional's Product Manager Software is included with the DN-700R for single point control of multiple players from a PC/Mac over the network. Complete with full access to the Web Remote as well as unique power on/off capabilities that allow power on and power off sequences to be programmed remotely for single units or multiple units in groups.

## DN-700R

- Standard input level: 0.5 Vp-p
- Format: IEC-60958(COAXIAL)
- INPUT - Balanced Digital IN
  - Type: XLR (1:GND, 2:Hot, 3:Cold)
  - Input impedance: 110 Ω
  - Standard input level: 3.5 Vp-p
  - Format: IEC-60958(AES/EBU)
- OUTPUT - Balanced Analog L/R
  - Type: XLR (1:GND, 2:Hot, 3:Cold)
  - Load impedance: Over 600 Ω
  - Output level: +4 dBu at 600 Ω load
  - Maximum Output level: +24 dBu/+20 dBu/+18 dBu
- OUTPUT - Unbalanced Analog L/R
  - Type: RCA terminal
  - Load impedance: Over 10 kΩ
  - Output level: -10 dBV
  - Maximum output level: +10 dBV/+6 dBV/+4 dBV
- OUTPUT - Balanced Digital
  - Type: XLR (1:GND, 2:Hot, 3:Cold)
  - Output impedance: 110 Ω
  - Standard output level: 3.0 Vp-p
  - Format: IEC-60958(AES/EBU)
- OUTPUT - Unbalanced Digital
  - Type: RCA terminal
  - Output impedance: 75 Ω
  - Standard output level: 0.5 Vp-p
  - Format: IEC-60958(COAXIAL)
- OUTPUT - Headphone Out
  - 20 mW/32 Ω
- Other
  - Maximum storage capacity: Up to 2 TB
  - Maximum file size: 2 GB
  - Maximum number of files: 2000 files (for 1 folder)
  - Maximum number of folders: 1000 folders
  - Maximum number of folder hierarchies: 8 (under the root directory)
- Environmental
  - Operating temperature: 5 – 35 °C
  - Operating humidity: 25 – 85 %, no condensation
  - Storage temperature: -20 – 60 °C
- General
  - Power supply (U.S.A and Canada models): AC 120 V, 60 Hz
  - Power Supply (European, U.K and Asia/Pacific models): AC 230 V, 50/60 Hz
  - Power consumption: 30W (typical), 0.4W (standby)
  - Dimensions (L x W x H): 19" x 13" x 1.74" (483 x 330 x 44 mm)
  - Weight: 7 lbs 14.99 oz (3.6 kg)



**Rhox Áudio e Vídeo Profissional** - SIBS Quadra 2 conjunto C Lote 12  
 Brasília - DF - 71736.203 - Tel (61) 3051-5800  
<https://loja.rhox.com.br>