


www.denonpro.com

PHONE: [401] 658.3131 August 20, 2017



DN-306X 6-Channel mixer with Mic 1 Priority

Key Features:

- Six-channel mixer in one rack space
- XLR/TRS combo input jacks with phantom power
- Two XLR line outputs
- Master level control and 3-band equalizer
- Mic one priority control

Overview:

The DN-306X is a compact 6-channel mixer. It features combo XLR/TRS input jacks with switchable MIC, LINE, and phantom power along with two XLR line outputs. Added features include mic one priority and a 3-band equalizer on the output. The DN-306X is compact, versatile and ready to solve any number of audio installation challenges.

Specifications:

- Audio Specification
 - Signal-to-Noise Ratio: > 94dB
 - Max Output Level: +24dBu
 - Inputs: (6) combo XLR/TRS
 - Phantom Power: 48VDC
 - Maximum Voltage Gain: 60dB
- Mic Inputs
 - Max Input Level: -20dBu
 - Sensitivity: -40dBu
 - Impedance: 1.4k Ω
- Line Inputs
 - Max Input Level: +24dBu
 - Impedance: 10k Ω
- Equalizer
 - High: \pm 15dB @ 12kHz
 - Mid: \pm 12dB @ 2.5kHz
 - Low: \pm 15dB @ 80Hz
- Environmental
 - Operating Temperature: 40 - 140°F (5 - 60°C)
 - Operating Humidity: 25 ~ 85% (non-condensing)
- General
 - Power Requirement: 100 ~ 240VAC 50/60Hz
 - Power Consumption: < 5W
 - Dimensions: 19.0 x 7.7 x 1.7" (483 x 195 x 44mm)
 - Weight: 5.6 lbs. (2.5 kg)