

AT8615

accessories



Microphone Desk Stand



Specifications

Input connector	3-pin XLRF-type
Output connector	3-pin XLRM-type
Mounting	Table-top with non-slip bottom pads
Dimensions	160.0 mm (6.29") maximum length, 130.0 mm (5.11") maximum width, 39.0 mm (1.53") maximum height

In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request. Specifications are subject to change without notice.

Features

- Quick-mount plug-in desk stand for 3-pin XLRM-type output
- Standard XLR-type input and output connectors
- Heavy die-cast construction
- Low-profile design with low-reflectance black finish for minimum visibility

Description

The AT8615 desk stand is a heavy-duty low-profile desk stand designed for tabletop applications. The sturdy metal base is equipped with three-pin XLRF-type input and three-pin XLRM-type output connector. It is designed to fit any gooseneck microphone with a three-pin XLRM-type output. The unit's heavy die-cast construction and non-slip pads help minimize coupling of surface vibration while the low profile design with low-reflectance black finish provides minimum visibility.

Architect's and Engineer's Specifications

The heavy desk stand base shall be designed to work with any dynamic gooseneck or phantom powered condenser gooseneck microphone with an integral 3-pin XLRM-type output connector. The unit shall offer a 3-pin XLRF-type input connector and a 3-pin XLRM-type connector for audio output. The unit shall offer a low-reflectance black finish. The unit's dimensions shall be: 160.0 mm (6.29") maximum length, 130 mm (5.11") maximum width, 39.0 mm (1.53") maximum height.

The Audio-Technica AT8615 is specified.

